



CERTIFICATE NUMBER 18-HG1720149-PDA
EFFECTIVE DATE 26 March 2018
EXPIRATION DATE 25 March 2023
ABS TECHNICAL OFFICE
Hamburg Engineering Department

CERTIFICATE OF

Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

VOSS FLUID GMBH

located at

**Luedenscheider Str. 52-54
D-51688 Wipperfuerth
Germany**

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product Pipe Fitting, Flared


Model 10° Flared Couplings

This Product Design Assessment (PDA) Certificate remains valid until expiration date or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau of Shipping


Dagmar Gramatzki,
Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010).

VOSS FLUID GMBH

LUEDENSCHIEDER STR. 52-54

D-51688 WIPPERFUERTH

Germany

Telephone: 49-2267-635657

Fax: 49-2267-639657

Email: fluid@voss.net

Web: www.voss.net

Tier: 3 - Type Approved, unit certification not required

Product: Pipe Fitting, Flared
Model: 10° Flared Couplings
Intended Service:
For use in steel piping systems.

Description:

Materials: steel, stainless steel.

Flared cones, clamping rings, flare connection parts (complete), adjustable couplings (stud/ standpipe adapter type), reducing couplings with taper and O-ring, straight couplings with taper and O-ring, gauge couplings.

Rating:

Series L (light): 6 to 10 mm OD for 500 bar, 12 to 18 mm OD for 400 bar, 22 to 42 mm OD for 250 bar.

Series S (heavy): 6 to 10 mm OD for 800 bar, 12 to 16 mm OD for 630 bar, 20 to 38 mm OD for 420 bar.

Operating temperatures depending on coupling and sealing materials, as per manufacturer's specification (see also under Comments).

Service Restriction:

- Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.
- Coupling types with tapered pipe threads are not to be used for toxic and corrosive fluid services and for all services of temperatures exceeding 495°C.
- The flared type tube connections are not to be used for pipe sizes above 60.3 mm in Class I and Class II piping systems.
- Straight-thread O-ring type fittings may be used for connections to equipment in hydraulic oil piping, without pressure and service limitation, but are not to be used for joining sections of pipes.
- For operating temperatures at lower than -18°C all materials used are to be certified for their adequate notch toughness properties.

Comments:

- The manufacturer has provided a declaration about the control of, or the lack of asbestos in this product.
- The above maximum working pressures are less than or equal to 1/4 burst pressure. In order to retain this safety factor of four (4), the specified maximum working pressures may be reduced depending on operating temperatures, high pressure surges etc.
- The application and installation of the couplings is to be in accordance with manufacturer's specifications and instructions and is to be approved in conjunction with the relevant systems.

Notes/Drawing/Documentation:

Document No. 214_06_1, Test Report of 27 Nov 2006_Voss - Burst_Vacuum_Extraction_2S plus_ES-4_VOSSForm_BV-10_DK, Revision: -, Pages: 26.

Document No. Assembly instruction BV-10, Assembly instruction BV-10, Revision: -, Pages: 5.

Document No. Burst_BV-10_DKO_2011031_German, Test Report of 21 Mar 2011_Voss - Burst Pressure, Revision: -, Pages: 12.

Document No. DS BV-10 tube connecting parts, Data sheet BV-10 tube connecting parts, Revision: -, Pages: 7.

Document No. Fire_ES-4_VOSSForm_BV-10_DKO_61070_English, Test Report of 21 Sep 2006_WPD - Fire Resistance, Revision: -, Pages: 8.

Document No. Product information BV-10, Product information BV-10, Revision: -, Pages: 3.

Document No. Pulsation-Vibration_ES-4_VOSSForm_BV-10_DKO_C10106_Englis, Test Report of 7 Dec 2006_IMA - Pressure, Revision: -, Pages: 24.

Document No. TD BV-10, Technical Drawings, Revision: -, Pages: 3.

Document No. VOSS Fluid ISO 14001_2015, ISO 14001_2015 Certificate, Revision: -, Pages: 3.

Document No. VOSS Fluid ISO 50001_2011, ISO 50001_2011 Certificate, Revision: -, Pages: 1.

Document No. VOSS Fluid ISO 9001_2015, ISO 9001_2015 Certificate, Revision: -, Pages: 1.

VOSS FLUID GMBH

LUEDENSCHIEDER STR. 52-54

D-51688 WIPPERFUERTH

Germany

Telephone: 49-2267-635657

Fax: 49-2267-639657

Email: fluid@voss.net

Web: www.voss.net

Tier: 3 - Type Approved, unit certification not required

Terms of Validity:

This Product Design Assessment (PDA) Certificate 18-HG1720149-PDA, dated 26/Mar/2018 remains valid until 25/Mar/2023 or until the Rules or specifications used in the assessment are revised (whichever occurs first).

This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product.

Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA.

Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

2018 Rules for Building and Classing Steel Vessels: 1-1-4/7.7, 1-1-Appendix 3 and 4, 4-6-1/7, 4-6-2/3, 4-6-2/5.5, 4-6-2/5.9.

National:

DIN 2353:2013-01, DIN 3870:2001-09, DIN 3861:2016-09.

International:

ISO 8434-1:2007-09.

Government:

NA

EUMED:

NA

OTHERS:

NA